

MATERIAL SAFETY DATA SHEET

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

1.1 Product identifier

Product name ARGON 4.2, COMPRESSED

Synonym(s) • ARGON 4.2

1.2 Uses and uses advised against

Use(s) ANALYTICAL CHEMISTRY ● FOOD APPLICATION(S) ● INDUSTRIAL APPLICATIONS ● SHIELDING GAS

FOR WELDING

1.3 Details of the supplier of the product

Supplier name WA GASES PTY LTD

Address 11 Longitude Avenue Neerabup, Western Australia 6031

Telephone 0472 686 009

Fax

Website <u>www.wagases.com.au</u>

1.4 Emergency telephone number(s)

Emergency 000

2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS (GHS ONLY) ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

GHS classification(s) Gases Under Pressure: Compressed gas

2.2 Label elements

Signal word WARNING



Pictogram(s)

Hazard statement(s)

H280 Contains gas under pressure; may explode if heated.

Prevention statement(s)

None allocated.

Response statement(s)

None allocated.

Storage statement(s)

P410 + P403 Protect from sunlight. Store in a well-ventilated place.

Disposal statement(s)

None allocated.

2.3 Other hazards

SDS Date: 18/05/2022

Page 1 of 7

Asphyxiant. Effects are proportional to oxygen displacement.

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
ARGON	7440-37-1	231-147-0	>99.995%

4. FIRST AID MEASURES

4.1 Description of first aid measures

Eye None required.

Inhalation If inhaled, remove from contaminated area. To protect rescuer, use an Air-line respirator or Self Contained Breathing

Apparatus (SCBA). Apply artificial respiration if not breathing. Give oxygen if available. For advice, contact a

Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor.

Skin None required.

Ingestion Ingestion is not considered a potential route of exposure.

First aid facilities None allocated.

4.2 Most important symptoms and effects, both acute and delayed

In high concentrations may cause asphyxiation. Symptoms may include loss of mobility / consciousness. Victim may not be aware of asphyxiation.

4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

5. FIRE FIGHTING MEASURES

5.1 Extinguishing media

Use water fog to cool containers from protected area.

5.2 Special hazards arising from the substance or mixture

Non flammable.

5.3 Advice for firefighters

Temperatures in a fire may cause cylinders to rupture. Cool cylinders or containers exposed to fire by applying water from a protected location. Remove cool cylinders from the path of the fire. Evacuate the area if unable to keep cylinders cool. Do not approach cylinders or containers suspected of being hot.

5.4 Hazchem code

2T

2 Fine Water Spray.

T Wear full fire kit and breathing apparatus. Dilute spill and run-off.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

If the cylinder is leaking, evacuate area of personnel. Inform manufacturer/supplier of leak. Use Personal Protective Equipment (PPE) as detailed in Section 8 of the SDS.

6.2 Environmental precautions

Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

6.3 Methods of cleaning up

Carefully move material to a well ventilated remote area, then allow to discharge if safe to do so. Do not attempt to repair leaking valve or cylinder safety devices.

6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Use of safe work practices are recommended to avoid inhalation. Do not drag, drop, slide or roll cylinders. The uncontrolled release of a gas under pressure may cause physical harm. Use a suitable hand truck for cylinder movement.

7.2 Conditions for safe storage, including any incompatibilities

Cylinders should be stored below 45°C in a secure area, upright and restrained to prevent cylinders from falling. Cylinders should also be stored in a dry, well ventilated area constructed of non-combustible material with firm level floor (preferably concrete), away from areas of heavy traffic and emergency exits.

7.3 Specific end use(s)

No information provided.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Exposure standards

	Reference	T VA		STEL	
Ingredient		ppm	mg/m³	ppm	mg/m³
Argon	SWA (AUS)	Asphyxiant			

Biological limits

No biological limit values have been entered for this product.

8.2 Exposure controls

Engineering controls Provide suitable ventilation to minimise or eliminate exposure. Confined areas (e.g. tanks) should be adequately ventilated or gas tested.

PPE

Eye / Face Wear safety glasses. **Hands** Wear leather gloves.

Body Wear coveralls and safety boots.

Respiratory Where an inhalation risk exists, wear Self Contained Breathing Apparatus (SCBA) or an Air-line respirator.









9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

AppearanceCOLOURLESS GASOdourODOURLESSFlammabilityNON FLAMMABLEFlash pointNOT RELEVANT

Boiling point -185.9°C

Melting pointNOT AVAILABLEEvaporation rateNOT APPLICABLEpHNOT APPLICABLEVapour densityNOT AVAILABLESpecific gravityNOT APPLICABLE

Vapour density Specific gravity Solubility (water) 0.0337 cm³/cm³ Vapour pressure NOT AVAILABLE Upper explosion limit NOT RELEVANT Lower explosion limit NOT RELEVANT Partition coefficient **NOT AVAILABLE** Autoignition temperature **NOT AVAILABLE** Decomposition temperature **NOT AVAILABLE**

9.1 Information on basic physical and chemical properties

Viscosity

Explosive properties

Oxidising properties

Odour threshold

NOT AVAILABLE

NOT AVAILABLE

NOT AVAILABLE

9.2 Other information

% Volatiles 100 % Critical pressure 4864 kPa

Critical temperature -122.4°C (Permanent gas)

Cylinder pressure (when full) 13000 kPa to 30000 kPa @ 15°C

Density 1.38 (Air = 1)

10. STABILITY AND REACTIVITY

10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

10.2 Chemical stability

Stable under recommended conditions of storage.

10.3 Possibility of hazardous reactions

Polymerization will not occur.

10.4 Conditions to avoid

Avoid shock, friction, heavy impact and heat.

10.5 Incompatible materials

Compatible with most commonly used materials. Hazardous by-products may be produced when this gas/gas mixture is used in welding, cutting and associated processes.

10.6 Hazardous decomposition products

This material will not decompose to form hazardous products other than that already present.

11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

Skin Not classified as a skin irritant.

Eye Not classified as an eye irritant.

Sensitisation Not classified as causing skin or respiratory sensitisation.

MutagenicityNot classified as a mutagen.CarcinogenicityNot classified as a carcinogen.ReproductiveNot classified as a reproductive toxin.

STOT - single Asphyxiant. Effects are proportional to oxygen displacement. Over exposure may result in dizziness,

exposure drowsiness, weakness, fatigue, breathing difficulties and unconsciousness.

STOT - repeated

exposure

Not classified as causing organ damage from repeated exposure.

Aspiration Not applicable to gases and gas mixtures.

12. ECOLOGICAL INFORMATION

12.1 Toxicity

No ecological damage caused by this product.

12.2 Persistence and degradability

The product is expected to biodegrade and is not expected to persist for long periods in an aquatic environment.

12.3 Bioaccumulative potential This

product does not bioaccumulate.

12.4 Mobility in soil

The substance is a gas, not applicable.

12.5 Other adverse effects

Fume from fabrication processes which use this gas/gas mixture may be harmful to the environment.

13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Waste disposal Cylinders should be returned to the manufacturer or supplier for disposal of contents.

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
14.1 UN Number	1006	1006	1006
14.2 Proper Shipping Name	ARGON, COMPRESSED	ARGON, COMPRESSED	ARGON, COMPRESSED
14.3 Transport hazard class	2.2	2.2	2.2
14.4 Packing Group	None allocated.	None allocated.	None allocated.

14.5 Environmental hazards

No information provided.

14.6 Special precautions for user

 Hazchem code
 2T

 GTEPG
 2C1

 EMS
 F-C, S-V

Other information

Ensure cylinder is separated from driver and that outlet of relief device is not obstructed.

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poison schedule A poison schedule number has not been allocated to this product using the criteria in the Standard for the

Uniform Scheduling of Medicines and Poisons (SUSMP).

Classifications Safework Australia criteria is based on the Globally Harmonised System (GHS) of Classification and

Labelling of Chemicals.

The classifications and phrases listed below are based on the Approved Criteria for Classifying Hazardous

Substances [NOHSC: 1008(2004)].

Hazard codes None allocated.

Risk phrases None allocated.

Safety phrases None allocated.

Inventory listing(s) AUSTRALIA: AICS (Australian Inventory of Chemical Substances)

All components are listed on AICS, or are exempt.

16. OTHER INFORMATION

Additional information

The storage of significant quantities of gas cylinders must comply with AS4332 The storage and handling of gases in cylinders. When using this gas/gas mixture for welding, cutting and associated processes, additional hazards may be generated by the process such as radiation, noise and fume. Risk assessments should be made for each activity to identify and quantify the individual hazards involved. Please refer to the BOC document "Welding Hazards and Risk Management" available from www.boc.com and refer to the relevant Safety Data Sheets for the welding consumables being used or, if available, the materials being welded.

APPLICATION METHOD: Gas regulator of suitable pressure and flow rating fitted to cylinder or manifold with low pressure gas distribution to equipment.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Abbreviations ACGIH American Conference of Governmental Industrial Hygienists

CAS # Chemical Abstract Service number - used to uniquely

CNS identify chemical compounds EC No. Central Nervous System

EMS EC No - European Community Number

Emergency Schedules (Emergency Procedures for Ships

GHS Carrying Dangerous Goods)
GTEPG Globally Harmonized System

IARC Group Text Emergency Procedure Guide
LC50 International Agency for Research on Cancer

LD50 Lethal Concentration, 50% / Median Lethal Concentration

mg/m³ Lethal Dose, 50% / Median Lethal Dose

OEL Milligrams pH per Cubic Metre

ppm Occupational STEL Exposure STOT-RE Limit

STOT-SE relates to hydrogen ion concentration using a scale of 0

SUSMP (high acidic) to 14 (highly alkaline).

SWA Parts Per Million

TLV Short-Term Exposure Limit

TWA Specific target organ toxicity (repeated exposure)

Specific target organ toxicity (single exposure)

Standard for the Uniform Scheduling of Medicines and

Poisons

Safe Work Australia Threshold Limit Value Time Weighted Average

[End of SDS]